

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-295521

(43)Date of publication of application : 10.11.1995

(51)Int.Cl.

G09G 3/36

G02F 1/133

(21)Application number : 06-107599

(71)Applicant : SONY CORP

(22)Date of filing : 22.04.1994


(72)Inventor : MAEKAWA TOSHIICHI
UCHINO KATSUhide

(54) ACTIVE MATRIX DISPLAY DEVICE AND ITS DRIVING METHOD

(57)Abstract:

PURPOSE: To suppress potential fluctuations of a video line accompanying an increase in sampling rate.

CONSTITUTION: The active matrix display device is equipped with row gate lines X, column signal lines Y, and liquid crystal pixels LC arranged at their intersection parts in a matrix. A V-driver 1 scans the respective gate lines X in sequence and selects liquid crystal pixels LC of one line at each horizontal period. An H-driver 4 samples a video signal VISG of each signal line Y and writes the video signal VSIG in the liquid crystal pixels LC of one line selected in each horizontal period. A precharging means 5 supplies a specific precharge signal VPS to the respective signal lines Y right before writing the video signal to the liquid crystal pixels LC of the one line. Consequently, the charging/ discharging capacity of each signal line Y is reducible when the video signal VSIG is sampled, and the potential fluctuations of the video line 2 can be suppressed.



LEGAL STATUS

[Date of request for examination]

27.04.2000

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3451717

[Date of registration] 18.07.2003

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office

BEST AVAILABLE COPY